Tube central FvTST

CÂBLE TÉLÉCOM 30 PAIRES, ISOLÉ PE, BLINDÉ, GAINE EXTÉRIEURE PVC



Description et application

Câbles à fibres optiques de type « loose Tube (tube lâche) » avec des fils en fibre de verre, un ruban en acier longitudinal ondulé et une double gaine thermoplastique LSZH.

1/0/1900

Construction

- Fibres optiques.
- Tube central en PBT rempli de gelée.
- Fils en fibre de verre.
- Gaine intérieure en thermoplastique LSZH.
- Ruban ondulé en acier revêtu de copolymère, appliqué longitudinalement avec chevauchement.
- Gaine extérieure en thermoplastique LSZH.
- Marquages: CABLESCOM / Année / Nombre de fibres / Type de fibre / Type de gaine / Marquages de longueur

Cables de Comunicaciones Zaragoza, SL.

Polígono de Malpica, calle D, nº 83. 50016 Zaragoza – Spain +34 976 729 900 | +34 976 729 974

www.cablescom.com | comercial@cablescom.com

Certified Company ISO 9001 – ISO 14001

All drawings, weights and dimensions details, as well as tube and fibre colours in this document are only indicative and must not be considered contractual.

MODULARITÉ 12 FO / TUBE

FO n°	2	4	6	8	12	16	24
N° Micromodules/Tubes	1	1	1	1	1	1	1
Poids (kg/km)	151	151	151	151	151	167	167
Diamètre extérieur nominal (mm)	11,7	11,7	11,7	11,7	11,7	12,4	12,4
Résistance maximale à la traction MAT (N)	1200 N						
	(εf<0.2%)						
Résistance aux chocs	5 J						
	300 mm, 3 impactos, Δα<0.05 dB						
Courbure	D=20 x Ø cable, Δα<0.05 dB						
Résistance à l'écrasement	3000 N, 10 cm						
Cycle thermique	-20ºC / 60ºC, Δα<0.05 dB						
Pénétration de l'eau	LPagua ≤ 3 m (24 horas)						
Épaisseur de la gaine / Diam FRP (mm)							

Cables de Comunicaciones Zaragoza, SL.

Polígono de Malpica, calle D, nº 83. 50016 Zaragoza – Spain +34 976 729 900 | +34 976 729 974

www.cablescom.com | comercial@cablescom.com

Certified Company ISO 9001 – ISO 14001

All drawings, weights and dimensions details, as well as tube and fibre colours in this document are only indicative and must not be considered contractual.