

MULTITUBE OPTICAL FIBRE CABLES TKT TYPE



Optic Fiber



UV resistant



Dielectric



Low smoke emission



Fire retardant



Zero halogen



ROHS compliant

STANDARDS

ADIF Standard 03.366.780.9 –5ª Edition.

Fibre: ITU-T G652D

DESCRIPTION AND APPLICATION

"Loose tube" singlemode optical fiber cables from 16 to 128 fibres for installation in tunnels or indoor with double reinforced LSZH sheath, fire retardant and halogen-free.

CONSTRUCTION

- **Central reinforcing element:** Dielectric fibreglass (FRP).
- **Loose tubes:** 4, 8 or 12 singlemode optical fibres in PBT loose tubes filled with thixotropic compound. Colour coding of tubes and fibres according to tables 1 and 2.
- **Core formation:** Loose tubes stranded in SZ. Swellable yarns and tapes to avoid water penetration and make the cable waterproof.
- **Inner sheath:** Fire retardant thermoplastic, low smoke emission and halogen free.
- **Reinforcement:** Aramid yarns as reinforcing element.
- **Outer sheath:** Fire retardant thermoplastic, black color, UV resistant, low smoke emission and halogen free.
- **Sheath marking :** The cable sheath will be marked with white ink at regular intervals with the following information :
 - *CABLESCOM/year/No.fibres/Batch number/MN/sheath type/length markings/ADIF*
 - *Other sheath marks available upon request*



OPTICAL FIBRE CHARACTERISTICS

The parameters of the optical fibres are compliant with the ITU-T G.652D recommendation.

See our fibre product sheet for the characteristics of the fibre

Optical transmission characteristics of cabled fibre :

Attenuation coefficient:

Average / maximum at 1310 nm: 0,35 / 0,37 dB/km

Average / maximum at 1550 nm: 0,21 / 0,24 dB/km

PMD individual $\leq 0,30 \text{ ps/km}^{1/2}$, PMD average $\leq 0,20 \text{ ps/km}^{1/2}$, PMD link $\leq 0,10 \text{ ps/km}^{1/2}$

Cut-off wavelength (λ_{cc}) $\leq 1250 \text{ nm}$

All drawings, designs, specifications and particulars of weights, dimensions, etc. in this documentation are only indicative and must not be considered contractual.

MULTITUBE OPTICAL FIBRE CABLES TKT TYPE

TABLE 1: LOOSE TUBES COLOUR CODE

		No fibres in the cable					
		16	32	64	96	128	
1st Layer	Tube	1	White	White	White	White	White
	2	White	Red	White	White	White	
	3	Red	Blue	Red	White	Red	
	4	Red	Green	Red	Red	Red	
	5	Blue	Black	Blue	Red	Blue	
	6	Blue	Black	Blue	Red	Blue	
	7	Green			Blue		
	8	Green			Blue		
	9				Blue		
	10				Green		
	11				Green		
	12				Green		
	2nd Layer	1					White
2						White	
3						Red	
4						Red	
5						Blue	
6						Blue	
7						Green	
8						Green	
9						Grey	
10						Grey	
11						Black	
12						Black	
Fibres per tube		2	8	5 of 12 1 of 4	8	8	

**Note: Black tubes are fillers*

TABLE 2: OPTICAL FIBERS COLOUR CODE

Fibre	1	2	3	4	5	6	7	8	9	10	11	12
Colour	Red	Green	Blue	Yellow	Violet	Orange	Brown	Grey	Black	Pink	Turquoise	White
Abrev.	R	G	Bl	Y	Vi	Or	Br	G	B	Pk	Tq	W

All drawings, designs, specifications and particulars of weights, dimensions, etc. in this documentation are only indicative and must not be considered contractual.

MULTITUBE OPTICAL FIBRE CABLES TKT TYPE

MECHANICAL AND ENVIRONMENTAL CHARACTERISTICS	Method	Test conditions
<i>Tensile strength</i> ($\Delta\epsilon_f=0\%$, $\Delta\alpha<0.05$ dB)	UNE-EN 60794-1-2 E1	3200 N
<i>Maximum tensile strength without breaking fibres</i>	UNE-EN 60794-1-2 E1	6200 N
<i>Torsion test</i> ($\Delta\alpha<0.05$ dB)	UNE-EN 60794-1-2 E7	$\pm 360^\circ$, L=1m, 50 cycles
<i>Repeated bending</i> ($\Delta\alpha<0.05$ dB)	UNE-EN 60794-1-2 E6	50 cycles, $\pm 180^\circ$
<i>Crush resistance</i> ($\Delta\alpha<0.05$ dB)	UNE-EN 60794-1-2 E3	2600 N, plate 10cm x 10cm
<i>Static bending</i> ($\Delta\alpha<0.05$ dB)	UNE-EN 60794-1-2 E11	D= 15 x \varnothing , 10 cycles
<i>Temperature cycling</i> (operation, $\Delta\alpha<0.05$ dB)	UNE-EN 60794-1-2 F1	-20°C / 70°C
<i>Water penetration</i>	UNE-EN 60794-1-2 F5	LP _{water} \leq 1 m (14 days)
<i>Vertical flame spread</i>	UNE-EN 60332	pass
<i>Vertical fire spread</i>	UNE-EN 50266	pass
<i>Corrosivity of the emitted gases</i>	UNE-EN 50267-2-1	pH \geq 4,3 y $\sigma \leq$ 10 μ S/mm
<i>Density of smoke</i>	UNE-EN 50268	Transmittance \geq 60 %

DIMENSIONS AND WEIGHT

Code	No. fibres	Diameter (mm)	Nominal Weight (kg/km)
EE5102F00001600N	16	12,9	190
EE5102F00003200N	32	14,2	210
EE5102F00006400N	64	14,2	220
EE5102F00009600N	96	19,3	350
EE5102F00012800N	128	20,0	370

All drawings, designs, specifications and particulars of weights, dimensions, etc. in this documentation are only indicative and must not be considered contractual.